

ACC558, ACC559*I-beam Clamps*

- Unit has 1-1/2"-11.5 NPT (38 mm) fitting for attachment of extension column

ACC558: for 4"-8" (101-203 mm) wide,
1/4" to 1" (6-25 mm) thick I-Beam
ACC559: for 7"-12" (177-304 mm) wide,
1/4" to 1" (6-25 mm) thick I-Beam

Max load: 250 lb (113 kg)
Ship Weight: **ACC558** 4.8 lb (2 kg)
ACC559 5.3 lb (2.4 kg)
Color: Black

**ACC557***Truss Ceiling Adapter*

- Attaches to a round square, rectangular, or I-Beam truss up to 3" (76 mm) wide x 3 1/2" (89 mm) high
- Unit has 1-1/2"-11.5 NPT (38 mm) fitting for attachment of extension column

Max load: 1200 lb (544 kg)
Ship Weight: 3 lb (1.4 kg)
Color: Black

**DCS200** *Structural Ceiling Plate with Stress Decoupler*

- Includes structural ceiling plate with integral high density rubber decoupler assembly to prevent vibrations
- Mounts to concrete beam, slab or other structural member
- Unit has 1-1/2"-11.5 NPT (38 mm) fitting for attachment of extension column

Max load: 300 lb (136 kg)
Ship Weight: 6 lb (2.7 kg)
Color: Black

**DCT100** *Truss Ceiling Adapter with Stress Decoupler*

- Includes truss ceiling plate with integral high density rubber decoupler assembly to prevent vibrations
- Attaches to round, square, rectangular or I-beam trusses up to 3" (76 mm) wide x 3 1/2" (89 mm) high
- Unit has 1-1/2"-11.5 NPT (38 mm) fitting for attachment of extension column

Max load: 300 lb (136 kg)
Ship Weight: 4 lb (1.8 kg)

**ACC600***Multi-display Interface Bracket*

- Suspends flat panel mount from extension column to in-line, curvilinear and circular MDJ multi-display configurations
- For use with EXT or ADJ model extension columns
- For other applications that require mounting from pipe larger than 2" (50 mm) in dia., use ACC557

Max load: 1200 lb (544 kg)
Ship Weight: 3.8 lb (1.7 kg)
Color: Black

**DCT500, DCT600, DCT700, DCT800, DCT900** *Multi-display I-beam Clamps*

- For use only with Peerless Multi-Display Systems in combination with Adjustable Length Extension Columns (ADD models)
- Includes structural ceiling plate with integral high density rubber decoupler assembly to prevent vibrations

DCT500: for 7"-12" (177-304 mm) wide,
.25"-1" (6-25 mm) thick I-beams
DCT600: for 15"-19.5" (381-495 mm) wide,
1.5"-2" (38-50 mm) thick I-beams
DCT700: for 15"-19.5" (381-495 mm) wide,
2.5"-3" (63-76 mm) thick I-beams
DCT800: for 7"-12" (177-304 mm) wide,
2.5"-3" (63-76 mm) thick I-beams
DCT900: for 4"-7" (101-177 mm) wide,
2.5"-3" (63-76 mm) thick I-beams

Max load: 600 lb (272 kg)
Ship Weight: **DCT500** 9.4 lb (4.3 kg)
DCT600 13.1 lb (6 kg)
DCT700 13.6 lb (6.2 kg)
DCT800 14 lb (6.4 kg)
DCT900 9 lb (4.1 kg)
Color: Black

**DCT300** *Multi-display Truss Ceiling Stress Decoupler*

- Includes truss ceiling plate with integral high density rubber decoupler assembly to prevent vibrations
- Attaches to round, square, rectangular or I-beam trusses up to 3" (76 mm) wide x 3 1/2" (89 mm) high
- Stub fitting accepts adjustable or fixed length ADD model extension columns

Max load: 1200 lb (544 kg)
Ship Weight: 4.6 lb (2.1 kg)
Color: Black

**DCS400** *Multi-display Structural Ceiling Stress Decoupler*

- Includes structural ceiling plate with integral high density rubber decoupler assembly to prevent vibrations
- Stub fitting accepts adjustable or fixed length ADD model extension columns

Max load: 1200 lb (544 kg)
Ship Weight: 7.8 lb (3.5 kg)
Color: Black

**PB-1***Plenum Box for CMJ450/453/455/500*

- Simple lockdown with slideable lid and optional lockdown screw
- 3" (76 mm) of lateral adjustment for precise placement
- 1/2" (13 mm), 3/4" (19 mm) and 1" (25 mm)
- For all CMJ450 & 453 installations ACC460 is required

Ship Weight: 11.28 lb (5.12 kg)
Color: White

